




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : <b>B01D 36/02, 17/02</b>		A1	(11) International Publication Number: <b>WO 00/27500</b>
			(43) International Publication Date: 18 May 2000 (18.05.00)
(21) International Application Number: PCT/US99/25562 (22) International Filing Date: 29 October 1999 (29.10.99) (30) Priority Data: 60/107,295 6 November 1998 (06.11.98) US (71) Applicant (for all designated States except US): STANADYNE AUTOMOTIVE CORP. [US/US]; 92 Deerfield Road, Wind- sor, CT 06095 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): MAXWELL, M., Craig [US/US]; 439 Helen Drive, Ripon, CA 95366 (US). (74) Agents: YALE, Guy, D. et al.; Alix, Yale & Ristas, LLP, 750 Main Street, Hartford, CT 06103 (US).		(81) Designated States: US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.	

(54) Title: FUEL FILTER SYSTEM WITH WATER BLEED AND WATER TRAP



## (57) Abstract

A fuel filter system employs a first filter (12) to separate water from the fuel and a second filter (38) which receives the water portion from the first filter (12) and removes the water from residual fuel with the use of hygroscopic material (42) and recycles the residual fuel back to the fuel tank (16).

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## **FUEL FILTER SYSTEM WITH WATER BLEED AND WATER TRAP**

### **Background of the Invention**

5 This invention relates generally to fuel filter systems employed in connection with internal combustion engines. More particularly, the present invention relates to fuel filter systems for removing foreign particles and separating water from the fuel supply or oil system of an internal combustion engine.

10 The absence of high standards of quality control in diesel fuel supplies dictates that an effective fuel filter be incorporated into the fuel supply system for a diesel engine. It is not uncommon for diesel fuel to have significant quantities of abrasive particles and water. The abrasive particles present the potential for permanent damage to components of the fuel injection pump. The abrasive particles can also adversely effect  
15 the performance of the pump by destroying the ability of the fuel injection pump to precisely meter and deliver fuel at high pressures. The presence of water in the diesel fuel supply can cause rusting of engine components, and during freezing conditions, can result in interruption of the fuel injection system and/or seizure of moving  
20 components.

A number of conventional fuel filters perform the dual function of removing particulate material from the diesel fuel and separating water from the fuel. Commonly, such fuel filters employ a disposable filter cartridge which is replaced at pre-established intervals of filter usage.  
25 Typically, a disposable filter/water separator cartridge is releasably secured to a base. A multi-stage filter assembly within the cartridge includes filtering and coalescing media and separates an upper portion of the chamber from a lower portion which functions as a water collection sump. The fuel filter may also feature a sensing device in the  
30 base to indicate the presence of a predetermined quantity of water in the sump. A petcock allows the water to be removed from the sump.

### Summary of the Invention

Briefly stated, the invention in a preferred form is a fuel filter system for removing foreign particles and separating water from the fuel supply of an internal combustion engine. The fuel filter system includes  
5 a first filter having a filter element that separates water from the fuel. The water collects in a sump in the lower portion of the first filter and exits the sump via an outlet. A second filter includes an enclosure having an inlet in fluid communication with the outlet of the first filter and an outlet in fluid communication with the fuel tank. A filter element  
10 composed of a hygroscopic material is contained in the enclosure. The water is absorbed by the hygroscopic material and any fuel that is entrained in the water is returned to the fuel tank via a return line.

The volume of the hygroscopic material increases as it absorbs water, restricting flow through the second filter and increasing the  
15 pressure inside the second filter and the waste line connecting the first and second filters. A pressure sensor monitors the pressure inside the second filter and sends a signal when the pressure reaches a predetermined level, indicating that the second filter must be changed. A pressure relief valve in the waste line has a setpoint below the first  
20 filter nominal pressure and above the signal pressure, thereby ensuring that there is no back flow from the second filter.

An object of the invention is to provide a new and improved fuel filter system.

Another object of the invention is to provide a new and improved  
25 fuel filter system having apparatus that facilitates disposal of water that is separated from the fuel.

A further object of the invention is to provide a new and improved fuel filter system having apparatus that reduces the cost of disposing water that is separated from the fuel.

30 Other objects and advantages of the invention will become apparent from the drawings and specification.

**Brief Description of the Drawing**

The present invention may be better understood and its numerous objects and advantages will become apparent to those skilled in the art by reference to the accompanying drawing which is a schematic diagram of a fuel filter system in accordance with the invention showing the fuel filter and clean-up filter with a portion of the enclosures removed.

**Detailed Description of the Preferred Embodiment**

With reference to the drawing, a fuel filter system in accordance with the present invention is generally designated by the numeral 10. Fuel filter system 10 comprises a fuel filter 12 having a fuel inlet 14 in fluid communication with the fuel tank 16 via a first fuel line 18 and a fuel outlet 20 in fluid communication with the fuel injection pump 22 via a second fuel line 24. A fuel lift pump 26 may be disposed in the first fuel line 18, intermediate the fuel tank 16 and the fuel filter 12, to ensure that there is an adequate flow of fuel to the fuel filter 12.

The fuel filter 12 is especially adapted for incorporation into the fuel supply system of an internal combustion engine (not illustrated), such as a diesel engine. The fuel filter 12 employs a filter element 28, such as a dual stage filter element or a single stage element, for removing particulate matter from the fuel and separating the water from the fuel. Filters of this type may also be used to filter impurities from oil in the lubricating system of an internal combustion engine. The filter element 28 is housed in an enclosure 30 having a sump 32 in its lower section to collect water which coalesces from the fuel. A waste line 34 in fluid communication with the sump 32 via a waste outlet 36 in the enclosure 30 provides a path means for draining the water from the fuel filter 12.

A constant bleed clean-up filter 38 is in fluid communication with the waste line 34 via an inlet 40. The clean-up filter 38 is provided to separate the fuel component from the water component of the

water/fuel mixture that exits the fuel filter 12 via the waste line. The clean-up filter 38 contains a hygroscopic water-absorbing filter media 42, such as corn starch, fiberglass/cellulose, or similar material known in the art, that removes the water from the water/fuel mixture. The fuel  
5 is returned to the fuel tank 16 via a return line 44 connected to the outlet 46 of the clean-up filter 38. The filter media 42 dimensionally expands as it absorbs the water, restricting the flow of fluid within the clean-up filter 38 and raising the pressure of the water/fuel mixture. A pressure detector 48 senses the pressure inside the clean-up filter 38,  
10 and a pressure switch 50 sends a signal proportional to the clean-up filter pressure to an alarm/gage 54. When the clean-up filter pressure reaches a predetermined level, the alarm/gage provides an indication that the clean-up filter 38 must be changed. A pressure relief valve 52 in the waste line 34 has a setpoint below the fuel filter nominal  
15 pressure and above the pressure that actuates the clean-up indication, preventing back-flow into the fuel filter 12 due to high pressure in the clean-up filter 38.

Circulating the water/fuel mixture through the clean-up filter 38 allows the majority of the fuel in the mixture to be recovered and  
20 recirculated to the fuel tank 16. Only a small amount of fuel is contained within the clean-up filter 38 when it is removed. Consequently, a fuel filter system 10 in accordance with the present invention reduces the amount of fuel that is removed from the fuel supply system when the water is removed from the fuel supply system.  
25 Such operation provides for more efficient use of the fuel and reduces disposal costs for the material that is removed from the fuel supply system.

While a preferred embodiment of the foregoing invention has been set forth for purposes of illustration, the foregoing description  
30 should not be deemed a limitation of the invention herein. Accordingly,

various modifications, adaptations and alternatives may occur to one skilled in the art without departing from the spirit and the scope of the present invention.

**What is claimed is:**

1. A fuel filter system for a fuel system having a fuel tank for storing fuel, the filter system comprising:
  - 5 a first filter comprising an inlet in fluid communication with the fuel tank, first filter means for separating water from the fuel, sump means for collecting the water, and an outlet in fluid communication with the sump means; and
  - 10 a second filter comprising an enclosure, an inlet in fluid communication with the outlet of the first filter, second filter means comprising a hygroscopic material for absorbing the water, and an outlet in fluid communication with the fuel tank.
2. The filter system of claim 1 wherein the second filter further comprises pressure sensing means for sensing the pressure in the enclosure of the second filter.
- 15 3. The filter system of claim 2 wherein the pressure sensing means comprises signal means for transmitting a signal proportional to the pressure in the enclosure of the second filter.
4. The filter system of claim 1 wherein the hygroscopic material has a volume, wherein the volume of the hygroscopic material increases as  
20 the hygroscopic material absorbs water.
5. The filter system of claim 1 further comprising passage means for providing fluid communication between the outlet of the first filter and the inlet of the second filter and pressure relief means disposed in the passage means.
- 25 6. The filter system of claim 1 wherein the hygroscopic material comprises corn starch.



7. A filter system for a liquid delivery system for an internal combustion engine, the liquid delivery system having a storage tank containing a mixture of a first liquid and a second liquid, the filter system comprising:

- 5           a first filter comprising an inlet in fluid communication with the storage tank, first filter means for separating the first liquid from the second liquid, sump means for collecting the first liquid, a first outlet for delivering the second liquid, and a second outlet in fluid communication with the sump means; and
- 10           a second filter comprising an enclosure, an inlet in fluid communication with the second outlet of the first filter, second filter means comprising an absorptive material for absorbing the first liquid, and an outlet in fluid communication with the fuel tank.

8. The filter system of claim 7 wherein the second filter further  
15 comprises pressure sensing means for sensing the pressure in the enclosure of the second filter.

9. The filter system of claim 8 wherein the pressure sensing means comprises signal means for transmitting a signal proportional to the pressure in the enclosure of the second filter.

20 10. The filter system of claim 7 wherein the absorptive material has a volume, wherein the volume of the absorptive material increases as the absorptive material absorbs the first liquid.

11. The filter system of claim 7 further comprising passage means for providing fluid communication between the outlet of the first filter and  
25 the inlet of the second filter and pressure relief means disposed in the passage means.

12. A fuel system comprising:  
a fuel storage tank;  
a first filter comprising an inlet in fluid communication with the fuel tank, first filter means for separating water from the fuel, sump means for collecting the water, a first outlet for delivering the fuel, and a second outlet in fluid communication with the sump means;  
a second filter comprising an enclosure, an inlet in fluid communication with the outlet of the first filter, second filter means comprising a hygroscopic material for absorbing the water, and an outlet in fluid communication with the fuel tank;  
a fuel injection pump having an inlet in fluid communication with first outlet of the first filter and an outlet.
13. The filter system of claim 12 wherein the second filter further comprises pressure sensing means for sensing the pressure in the enclosure of the second filter and for transmitting a signal proportional to the pressure in the enclosure of the second filter.
14. The filter system of claim 12 wherein the hygroscopic material has a volume, wherein the volume of the hygroscopic material increases as the hygroscopic material absorbs water.
15. The filter system of claim 12 further comprising passage means for providing fluid communication between the outlet of the first filter and the inlet of the second filter and pressure relief means disposed in the passage means.
16. The filter system of claim 12 further comprising a fuel lift pump having an inlet in fluid communication with the fuel storage tank and an outlet in fluid communication with the inlet of the first filter.




Fig. 1

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US99/25562

**A. CLASSIFICATION OF SUBJECT MATTER**

IPC(6) :B01D 36/02, 17/02

US CL :210/172, 314, 195.1, 196 ; 123/514, 509, 510

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 210/172, 314, 195.1, 196 ; 123/514, 509, 510

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

NONE

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4,795,556 A (BROTEA et al) 03 January 1989, see figure 5,6.	1-16
Y	US 4814087 A (TAYLOR) 21 March 1989, see figure 1.	1-16



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*B* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means	
*P* document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

31 JANUARY 2000

Date of mailing of the international search report

10 FEB 2000

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

  
THOMAS M. LITHGOW

Telephone No. 703-308-0661